

HyperGuard™ NXC3152

Product Data Sheet



Product Brief

HyperGuard™ NXC3152 is our Cut Level E glove for dry, wet, and oil environments. The embedded nitrile Super Grip® technology includes double dipping and sandy surface, which gives extra friction during oily material handling and keeps hand clean. Foam technology makes NXC3152 much lighter and softer.

Coating

Colour	Black
Material	Nitrile
Texture	Foam Sandy
Area	Palm

Liner

Gauge	13
Colour	Blue
Material	HPPE/steel/polyester

Dimensions

	Weight (g/pair) (±5%)	Length (mm)		Width (mm)		Palm thickness (mm) (±0.2)
		Glove (-5/+10)	Wrist (±5)	Palm (±4)	Wrist (±4)	
7"	67	230	77	92	75	1.65
8"	72.5	240	80	96	79	1.65
9"	80.5	250	83	100	83	1.65
10"	87	260	86	105	87	1.65
11"	96	270	89	112	90	1.65
12"	102	280	92	115	93	1.65

Packaging

Pairs per bag	12
Bags per carton	10
Carton dimensions (cm)	64*30*30



EN Test Results

EN 388:2016	4X42E
Abrasion	>8000 Cycles
Cut	>20
Tear	>75
Puncture	>60
Cut ISO	E

Applications

Automotive	Facility maintenance	Machinery & Equipment
Transportation & Warehousing	Construction	Glass & Building materials

Features

Cut Resistant	Abrasion Resistant	Strong Grip
---------------	--------------------	-------------