

HyperGuard™ NXC3157

Product Data Sheet



Product Brief

HyperGuard™ NXC3157 is our Cut Level F glove for dry, wet, and oil environments. The embedded nitrile Super Grip® technology includes double dipping and sandy surface, which gives extra friction during oily material handling and keeps hand clean. Foam technology makes NXC3157 much lighter and softer.

Coating

Colour	Black
Material	Nitrile
Texture	Foam Sandy
Area	Palm

Liner

Gauge	13
Colour	Camouflage
Material	Aramid fiber/steel

Dimensions

	Weight (g/pair) (±5%)	Length (mm)		Width (mm)		Palm thickness (mm) (±0.2)
		Glove (-5/+10)	Wrist (±5)	Palm (±4)	Wrist (±4)	
7"	79	230	78	93	77	1.72
8"	83	240	82	97	80	1.72
9"	91	250	85	103	83	1.72
10"	98	260	88	105	86	1.72
11"	108	270	91	112	88	1.72
12"	115	280	94	114	91	1.72

Packaging

Pairs per bag	12
Bags per carton	10
Carton dimensions (cm)	64*30*30



EN Test Results

EN 388:2016	4X43F
Abrasion	>8000 Cycles
Cut	>20
Tear	>75
Puncture	>100
Cut ISO	F

Applications

Automotive	Facility maintenance	Machinery & Equipment
Transportation & Warehousing	Construction	Glass & Building materials

Features

Cut Resistant	Abrasion Resistant	Strong Grip
---------------	--------------------	-------------