

HyperGuard™ NXC3150

Product Data Sheet



Product Brief

HyperGuard™ NXC3150 is our Cut Level D glove for dry, wet, and oil environments. The embedded nitrile Super Grip® technology includes double dipping and sandy surface, which gives extra friction during oily material handling and keeps hand clean. Foam technology makes NXC3150 much lighter and softer.

Coating

Colour	Black
Material	Nitrile
Texture	Foam Sandy
Area	Palm

Liner

Gauge	15
Colour	Light Blue
Material	HPPE/Steel/Glass/Polyester

Dimensions

	Weight (g/pair) (±5%)	Length (mm)		Width (mm)		Palm thickness (mm) (±0.2)
		Glove (-5/+10)	Wrist (±5)	Palm (±4)	Wrist (±4)	
6"	58	225	74	84	75	1.50
7"	64	235	77	90	78	1.50
8"	68	245	80	94	81	1.50
9"	74	255	82	98	84	1.50
10"	82	265	85	104	87	1.50
11"	90	275	88	111	90	1.50
12"	99	285	90	113	93	1.50

Packaging

Pairs per bag	12
Bags per carton	10
Carton dimensions (cm)	64*30*30



EN Test Results

EN 388:2016	4X42D
Abrasion	>8000 Cycles
Cut	X
Tear	>75
Puncture	>60
Cut ISO	D

Applications

Automotive	Facility maintenance	Machinery & Equipment
Transportation & Warehousing	Construction	Glass & Building materials

Features

Cut Resistant	Abrasion Resistant	Strong Grip
Oil Repellent		